

Transorfilter

Vacuum pump set

DUO 250



TRANSORFILTER

www.transorfilter.se

Sweden

Transorfilter, DUO 250 Vacuum pump set

Transorfilter vacuum pump set consists of a vacuum pump assembled on a steel frame with wheels. For air evacuation of power transformers.



Function

Transorfilter vacuum pump set consists of a vacuum pump assembled on a sturdy steel frame with wheels. The vacuum pump is equipped with exhaust filter, digital vacuum meter, mechanic vacuum meter, closable connection DN 100 ISO and a pressure warning system.

The pressure warning system give of sound and light signals when the pressure exceeds a preset value between 1-10 mbar.

Two vacuum hoses Ø100, L = 5m with connections DN 100 ISO are included with the equipment. Optionally hydraulic 3" hoses with camlock connections can be delivered on request. A protective plastic cover is also available as extra equipment.



Transorfilter, Technical Data

Technical data	1-stage 90	1-stage 230	2-stage 120	2-stage 250
Pump capacity:	90 m3/h	230 m3/h	120 m3/h	250 m3/h
Final pressure:	< 0,3 mbar	< 0,3 mbar	< 0,0013 mbar	< 0,0013 mbar
Voltage and frequency:	3 x 400V, 50Hz	3 x 400V, 50Hz	3 x 400V, 50Hz	3 x 400V, 50Hz
Motor effect:	2,2 kW	7,5 kW	4,0 kW	7,5 kW
Length:	1 500 mm	1 600 mm	1 500 mm	1 700 mm
Width:	750 mm	800 mm	750 mm	800 mm
Height:	1 250 mm	1 500 mm	1 250 mm	1 550 mm
Weight:	300 kg	550 kg	300 kg	550 kg

*** Other voltage and frequency specifications at your request.
Subject to changes without notice.

